

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) EP 1 069 630 A1

(12) EUROPEAN PATENT APPLICATION

(43) Date of publication:
17.01.2001 Bulletin 2001/03

(51) Int Cl.7: H01M 2/10, H02J 7/00

(21) Application number: 00306009.2

(22) Date of filing: 14.07.2000

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

- Larkin, Mary Elizabeth
Perry Hall, Maryland 21128 (US)
- Agnes, Michael J.
Bel Air, Maryland 21014 (US)

(30) Priority: 15.07.1999 US 354405

(71) Applicant: Black & Decker Inc.
Newark Delaware 19711 (US)

(74) Representative: Dlugosz, Anthony Charles et al
Black & Decker Europe
European Group Headquarters
210 Bath Road
Slough, Berkshire SL1 3YD (GB)

(72) Inventors:
• White, Paul S.
Ellicott City, Maryland 21043 (US)

(54) Battery pack

(57) In accordance with the present invention, an improved battery pack is employed. The battery pack includes a housing with opposing walls, a plurality of cells disposed within the housing, at least two terminals electrically connected to the cells, a latching mechanism disposed on each opposing wall for latching the battery pack to a cordless device, each latching mechanism including a latch and a button disposed on the wall for moving the latch between unlatching and latching posi-

tions, the latching buttons being disposed along a first plane, the first plane being substantially vertical, wherein the number of cells disposed along the first plane is smaller than the number of cells disposed along a second plane substantially parallel to the first plane. The battery pack may also include a stacked cell disposed on the plurality of cells. The stacked cell may be disposed along the first plane. However, the stacked cell is not included in the number of cells disposed along the first plane.




FIG. 4

EP 1 069 630 A1

Description

[0001] This invention relates generally to battery packs and, more particularly, to battery packs for cordless power tools.

[0002] Cordless products which use rechargeable batteries are prevalent throughout the workplace as well as in the home. From housewares to power tools, rechargeable batteries are used in numerous devices. Ordinarily, nickel-cadmium or nickel-metal hydride battery cells are used in these devices. Since the devices use a plurality of battery cells, the battery cells are ordinarily packaged as battery packs. These battery packs couple with the cordless devices and secure to the device. The battery pack may be removed from the cordless device and charged in a battery charger or charged in the cordless device itself.

[0003] FIGS. 1-3 illustrate a typical battery pack 10, which includes a bottom housing 11, a plurality of cells 12 disposed within the housing, a cell 13 disposed on the plurality of cells 12, and a terminal block 14 disposed on cell 13. Persons skilled in the art will recognize that the terminal block 14 and cells 12, 13 are electrically connected in a manner well known in the art, and that such electrical connections are not shown for the sake of clarity. Also, persons skilled in the art are referred to US Patent No. 5,144,217 for further information on a typical prior art terminal block 14.

[0004] A pack cover 15 carrying a tower 16 is disposed on housing 11 so as to contain cells 12, 13 therein. Tower 16 has an aperture 17 exposing terminal block 14 for electrical connection to the power tool (not shown). The pack cover 15 may be held in place via screws 19, or other means, so as adhesives, molten plastic, etc.

[0005] Typical battery packs include at least one latch mechanism 18 for latching the battery pack 10 to the power tool, or cordless device. Latch mechanism 18 typically includes a button 18B disposed on housing 11, a latch hook 18L movably connected to button 18B and movable between a latching position and an unlatched position, and a spring 18S for biasing latch hook 18L towards the latching position. Accordingly, in order to unlatch a battery pack from the power tool, the user needs to press button(s) 18B with one hand, moving latch hook 18L towards the unlatched position, and pull out the battery pack 10, while holding the power tool with the other hand.

[0006] Typically battery packs 10 have two buttons 18B on opposing walls of housing 11. Accordingly, the operator needs to bridge the composite distance of A, B and C, i.e., the lengths along the housing 11, in order to press both buttons 18B and unlatch battery pack 10. However, as the number of cells 12 is increased to obtain higher voltages, the composite distance (A+B+C) is also increased, until the operator cannot easily reach both buttons 18B.

[0007] In accordance with the present invention, an

improved battery pack is employed. The battery pack includes a housing with opposing walls, a plurality of cells disposed within the housing, at least two terminals electrically connected to the cells, a latching mechanism disposed on each opposing wall for latching the battery pack to a cordless device, each latching mechanism including a latch and a button disposed on the wall for moving the latch between unlatching and latching positions, the latching buttons being disposed along a first plane, the first plane being substantially vertical, wherein the number of cells disposed along the first plane is smaller than the number of cells disposed along a second plane substantially parallel to the first plane. The battery pack may also include a stacked cell disposed on the plurality of cells. The stacked cell may be disposed along the first plane. However, the stacked cell is not included in the number of cells disposed along the first plane.

[0008] Additional features and benefits of the present invention are described, and will be apparent from, the accompanying drawings and the detailed description below.

[0009] The accompanying drawings illustrate preferred embodiments of the invention according to the practical application of the principles thereof, and in which:

FIG. 1 is an exploded perspective view of a prior art battery pack;

FIG. 2 is a rear view of the lower portion of the battery pack of FIG. 1;

FIG. 3 is a top plan view of the lower portion of FIG. 2 along line III-III;

FIG. 4 is a side view of a lower portion of the improved battery pack according to a first embodiment of the present invention;

FIG. 5 is a bottom plan view of the lower portion of FIG. 4 along line V-V;

FIG. 6 is a top plan view of the lower portion of FIG. 4 along line VI-VI;

FIG. 7 is a rear elevational view of the lower portion of FIG. 4 along line VII-VII; and

FIG. 8 is a side view of a lower portion of the improved battery pack according to a second embodiment of the present invention.

[0010] The invention is now described with reference to the accompanying figures, wherein like numerals designate like parts. Referring to FIGS. 4-7, the battery pack 100 has a housing 11A, latch mechanisms 18 thereon, and cells 12 within housing 11A. Battery pack 100 may also have a pack cover 15, tower 16, terminal block 14 and/or cell 13 as taught in the prior art.

[0011] Preferably each of two opposing walls of housing 11A has a front portion 11F, a rear portion 11R and a channel portion 11C disposed between front and rear portions 11F, 11R. Preferably channel portion 11C is depressed relative to front and rear portions 11F, 11R. In

other words, while front and rear portions 11F, 11R may be substantially coplanar, channel portion 11C is not.

[0012] Channel portion 11C may include a surface 11S. Preferably the distance between surface 11S and center plane Z is smaller than the distance between center plane Z and front and/or rear portions 11F, 11R. Surface 11S may be inclined or substantially parallel to front and/or rear portions 11F, 11R (though not coplanar).

[0013] Persons skilled in the art will recognize that button 18B may be disposed on surface 11S or within channel portion 11C. However, persons skilled in the art should recognize that buttons 18B may be disposed outside of channel portion 11C.

[0014] By providing such channel portions 11C, the effective distance between latch buttons 18B, i.e., the composite distance, is about D+E+F, and thus is smaller than composite distance A+B+C, thus providing a more ergonomic access to the latching buttons 18B. Preferable, distance D+E+F is about or less than 4 inches, whereas the distance A+B+C is about 4.5 inches.

[0015] In order to obtain such arrangement, it is preferable to arrange cells 12 so that the number of cells 12 disposed between the latching buttons 18, or along plane X, is smaller than the number of cells 12 disposed elsewhere in housing Y, e.g., along plane Y. Such cell arrangement permits the surface 11S to be closer to the center plane Z.

[0016] A second embodiment is shown in FIG. 8, where like numerals refer to like parts. The teachings of the first embodiment are incorporated herein. Housing 11B, as before, may carry latching buttons 18B, and may have front and rear portions 11F, 11R. Housing 11B may also have a bottom surface 11BP, which is substantially planar along plane H. A channel portion 11D is preferably disposed between front and rear portions 11F, 11R, and/or below latching buttons 18B. Preferably, channel portion 11D has a surface 11DP which is disposed between buttons 18B and plane H. In other words, the distance between surface 11DP and buttons 18B is smaller than the distance between buttons 18B and plane H. Similarly, the distance between surface 11DP and top housing plane G is smaller than the distance between planes G and H, i.e., the height of housing 11.

[0017] In order to obtain such arrangement, it is preferable to arrange at least one of the cells 12 (cell 12H) so that it lays horizontally, as opposed to the other cells 12 which stand vertically, in housing 11. Such cell arrangement permits the surface 11DP to be closer to the buttons 18B, etc.

[0018] Housing 11 may also have vent holes 11H disposed thereon. In addition, housing 11 may have ribs 11R to help locate the cells 12 within housing 11. Preferably holes 11H are disposed between ribs 11R and/or the walls of housing 11.

[0019] Persons skilled in the art may recognize other alternatives to the means disclosed herein. However, all these additions and/or alterations are considered to be

equivalents of the present invention.

Claims

1. A battery pack (100) comprising:

a housing (11A) comprising opposing walls;
a plurality of cells (12) disposed within the housing (11A);
at least two terminals (14) electrically connected to the cells (12);
a latching mechanism (18) disposed on each opposing wall for latching the battery pack (100) to a cordless device, each latching mechanism (18) comprising a latch (18L) and a button (18B) disposed on the wall for moving the latch (18L) between unlatching and latching positions, the latching buttons (18B) being disposed along a first plane (X), the first plane (X) being substantially vertical;
wherein number of cells (12) disposed along the first plane (X) is smaller than number of cells (12) disposed along a second plane (Y) substantially parallel to the first plane (X).

2. A battery pack (100) as claimed in claim 1, wherein at least one wall has first (11F or 11R) and second (11C) portions.

3. A battery pack (100) as claimed in claim 2, wherein at least one of the buttons (18B) is disposed on the second portion (11C) of the at least one of the walls.

4. A battery pack (100) as claimed in either one of claims 2 or 3, wherein the first (11F or 11R) and second (11C) portions comprise substantially non-coplanar surfaces.

5. A battery pack (100) as claimed in claim 4, wherein distance between the second portion surface (11C) and a center plane (Z) dissecting the housing (11A) is smaller than distance between the first portion surface (11F or 11R) and the center plane (Z).

6. A battery pack (100) as claimed in any one of the preceding claims, wherein at least one of the cells (12), and preferably each of the cells (12), is vertical.

7. A battery pack (100) as claimed in any one of the preceding claims, wherein the housing (11A) comprises a floor which is preferably substantially horizontal.

8. A battery pack (100) as claimed in claim 7, wherein the latching buttons (18B) are disposed along a first line located at a first distance from the floor.

9. A battery pack (100) as claimed in claim 8, wherein distance between the latching buttons (18B) along periphery of the housing (11A) is smaller than distance between two points along periphery of the housing (11A), the two points being contained within a second line parallel to the first line and located at the first distance from the floor.
10. A battery pack (100) comprising:
 a housing (11A) comprising opposing walls, at least one of the walls having first (11F or 11R) and second (11C) portions, the first (11F or 11R) and second (11C) portions comprising substantially non-coplanar surfaces, the housing (11A) being dissected by a center plane (Z);
 a plurality of cells (12) disposed within the housing (11A);
 at least two terminals (14) electrically connected to the cells (12);
 a latching mechanism (18) disposed on the housing (11A) for latching the battery pack (100) to a cordless device, the latching mechanism (18) comprising a latch (18L) and a button (18B) disposed on the second portion (11C) for moving the latch (18L) between unlatching and latching positions;
 wherein distance between the second portion surface (11C) and the center plane (Z) is smaller than distance between the first portion surface (11F or 11R) and the center plane (Z).
11. A battery pack (100) as claimed in claims 10, wherein at least one of the cells (12), and preferably each of the cells (12), is vertical.
12. A battery pack (100) as claimed in either one of claims 10 or 11, wherein the housing (11A) comprises a floor which is preferably substantially horizontal.
13. A battery pack (100) as claimed in any one of claims 10 to 12, further comprising a latching button (18B) on the other wall.
14. A battery pack (100) as claimed in claim 13, wherein the latching buttons (18B) are disposed along a first line located at a first distance from the floor.
15. A battery pack (100) as claimed in claim 14, wherein distance between the latching buttons (18B) along periphery of the housing (11A) is smaller than distance between two points along periphery of the housing (11A), the two points being contained within a second line parallel to the first line and located at the first distance from the floor.
16. A battery pack (100) as claimed in any one of claims 13 to 15, wherein number of cells (12) disposed along a first plane (X) between the latching buttons (18B) is smaller than number of cells (12) disposed along a second plane (Y) substantially parallel to the first plane (X).
17. A battery pack (100) comprising:
 a housing (11A) comprising a floor and opposing walls connected to the floor, at least one wall having first (11F or 11R) and second (11C) portions;
 a plurality of cells (12) disposed within the housing (11A);
 at least two terminals (14) electrically connected to the cells (12);
 a latching mechanism (18) disposed on each opposing wall for latching the battery pack (100) to a cordless device, each latching mechanism (18) comprising a latch (18L) and a button (18B) disposed on each wall for moving the latch (18L) between unlatching and latching positions, the latching buttons (18B) being disposed along a first line located at a first distance from the floor;
 wherein distance between the latching buttons (18B) along periphery of the housing (11A) is smaller than distance between two points along periphery of the housing (11A), the two points being contained within a second line parallel to the first line and located at the first distance from the floor and in the first portion (11F or 11R).
18. A battery pack (100) as claimed in claim 17, wherein the first (11F or 11R) and second (11C) portions comprise substantially non-coplanar surfaces.
19. A battery pack (100) as claimed in claim 18, wherein distance between the second portion surface (11C) and a center plane (Z) dissecting the housing (11A) is smaller than distance between the first portion surface (11F or 11R) and the center plane (Z).
20. A battery pack (100) as claimed in any one of claims 17 to 19, wherein at least one of the cells (12), and preferably each of the cells (12), is vertical.
21. A battery pack (100) as claimed in any one of claims 17 to 20, wherein number of cells (12) disposed along a first plane (X) between the latching buttons (18B) is smaller than number of cells (12) disposed along a second plane (Y) substantially parallel to the first plane (X).
22. A battery pack (100) comprising:
 a housing (11B) comprising a first portion (11F

or 11R) having a first floor (11BP) and first and second walls connected to the first floor (11BP), and a second portion (11D) having a second floor (11DP) and third and fourth walls connected to the second floor (11DP), where the first and second floors are non-coplanar; a plurality of cells (12) disposed within the housing (11B); and at least two terminals (14) electrically connected to the cells (12).

23. A battery pack (100) as claimed in claim 22, further comprising first and second latching mechanisms (18) disposed on the housing (11B) for latching the battery pack (100) to a cordless device.

24. A battery pack (100) as claimed in claim 23, wherein each latching mechanism (18) comprises a latch (18L) and a button (18B) connected to the latch (18L) for moving the latch (18L) between unlatching and latching positions.

25. A battery pack (100) as claimed in claim 24, wherein at least one button (18B) is disposed on the second portion (11D).

26. A battery pack (100) as claimed in either one of claims 24 or 25, wherein the latching buttons (18B) are disposed along a first line (18BP) located at a first distance from first floor plane (H).

27. A battery pack (100) as claimed in claim 26, wherein distance between the latching buttons (18B) along periphery of the housing (11B) is smaller than distance between two points along periphery of the housing (11B), the two points being contained within a second line parallel to the first line and located at the first distance from the first floor plane (H).

28. A battery pack (100) as claimed in any one of claims 24 to 27, wherein number of cells (12) disposed along a first plane (X) between the latching buttons (18B) is smaller than number of cells (12) disposed along a second plane (Y) substantially parallel to the first plane (X).

29. A battery pack (100) as claimed in any one of claims 22 to 28, wherein the first (11F or 11R) and second (11D) portions comprise substantially non-coplanar surfaces.

30. A battery pack (100) as claimed in claim 29, wherein distance between the second portion surface (11D) and a center plane (Z) dissecting the housing (11B) is smaller than distance between the first portion surface (11F or 11R) and the center plane (Z).

31. A battery pack (100) as claimed in any one of claims

22 to 30, wherein at least one of the cells (12) is horizontal.

32. A battery pack (100) as claimed in any one of claims 22 to 30, wherein at least one of the cells (12) is vertical.

33. A battery pack (100) as claimed in any one of the preceding claims, further comprising a stacked cell (13) disposed on the plurality of cells (12).

34. A battery pack (100) as claimed in claim 33, wherein the stacked cell (13) is disposed along the first plane (X).

35. A battery pack (100) as claimed in claim 34, wherein the stacked cell (13) is not included in the number of cells (12) disposed along the first plane (X).

36. A battery pack (100) as claimed in any one of claims 2, or 10 to 35, wherein the first portion surface (11F or 11R) and /or second portion surface (11C or 11D) is substantially vertical.

37. A battery pack (100) as claimed in any one of claims 2, or 10 to 35, wherein the second portion surface (11C or 11D) is inclined.

38. A battery pack (100) as claimed in any one of claims 2, or 10 to 37, wherein at least one of the buttons (18B) is disposed on the second portion surface (11C or 11D) of the at least one of the walls.




FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 3
(PRIOR ART)




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 30 6009

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	US 5 213 913 A (ANTHONY III PHILIP M ET AL, LINDENHURST, US) 25 May 1993 (1993-05-25) * column 3, line 4 - column 5, line 22 * * figures 1-3 *	22-26	H01M2/10 H02J7/00
A	---	1-21	
D,A	US 5 144 217 A (GARDNER BILLY J ET AL, ROCKY MOUNT TARBORO, US) 1 September 1992 (1992-09-01) * figures 16,17 *	1-38	
A	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 07, 31 July 1997 (1997-07-31) & JP 09 073890 A (MAKITA CORP), 18 March 1997 (1997-03-18) * abstract *	1-38	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H01M H02J
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 November 2000	Examiner Peis, S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons</p> <p>& : member of the same patent family, corresponding document</p>			

CPD FORM 1500 02/02 (7-00-001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 30 6009

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-11-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5213913 A	25-05-1993	CA 2089944 A,C	22-08-1993
US 5144217 A	01-09-1992	US 5391972 A	21-02-1995
JP 09073890 A	18-03-1997	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82